

Introducing a new version of our ever-popular **Flush Mount Ring (FMR)** the **MPS-FMR-__MU-SD**. What this **Swing Down** version does is add the ability to pivot the frame along the lower edge providing access to the cables in the **screw-cover-wire-way** and to the rear of the connectors mounted in the **MPS** panels in the frame. This will ease initial installation and improves cable / connector access for future maintenance.



Each **MPS-FMR-__MU-SD** comes fully assembled ready to be installed to an existing 6" tall **Screw-Cover-Wire-Way** by way of the 2 slotted mounting holes in each of the end brackets using the supplied hardware, machine screws / nuts or self tapping screws.



As the pivot action relies on the mounting brackets installed to the **Screw-Cover-Wire-Way**, one at each end, it is recommended the length of the frame be limited to 28MU to avoid flex.

All that is needed to open the frame is to undo the 2 Thumb-screws located at either end.

What is shown above is an **MPS-FMR-7MU-SD** attached to a 6" tall **B-Line Screw-Cover-Wire-Way**

The **Swing Down** version of our **Flush Mount Ring** can be supplied in any length as long as it is in increments of 0.875" and no longer than 28MU / 24.50"

We can also supply an upgrade kit, **MPS-FMR-KIT-SD** to convert a standard **Flush Mount Ring** to a **Swing Down** version.



Visit our Website – www.signt.com – or give us a call at (949) 859-9615 for Information and pricing on all of our products. Thanks.